



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

NOVEMBER 2014

PRODUCT NAME

R10 Penetrating Oil

PRODUCT RANGE

Part Number	Available Size
CT-R10-300	400g Aerosol



Refer to MSDS for product safety guidelines

R10 Penetrating Oil

Chemtools® R10 Penetrating Oil is a mixture of refined low viscosity mineral oils. This oil is used to free rusted parts as it can penetrate into minute cracks between parts. It is also used for general maintenance of machinery and equipment. May also be used in marine environments for protection from salt spray deposits

Chemtools® R10 Revive-IT is flammable and should not be sprayed onto live electrical equipment or other sources of possible ignition. Allow fumes and vapours to disperse before starting up equipment.

Will not adversely affect rubber, paintwork ,or most plastics. May effect polystyrene and polycarbonates; test before applying.

FEATURES AND BENEFITS:

- Loosens rusted parts
- Lubricates
- Stops squeaks
- Protects against rust and corrosion
- Helps to start wet motors

TYPICAL APPLICATIONS:

- Rusted and dry locks, hinges, and bolts
- Agricultural and industrial equipment
- Electrical and mechanical tools
- Cleaning and protecting garden tools
- Hunting and fishing equipment
- Camping equipment
- Musical instruments
- Lubricating metal zippers
- Auto lighting fittings, cables, antenna, doors, etc

PHYSICAL PROPERTIES:

Flash Point	12°C
Boiling Point	82°C
Appearance	Clear Colourless Liquid
Odour	Paraffinic
Specific Gravity @ 20°C	0.787
Aerosol Propellant	Hydrocarbons

STORAGE:

Store in a cool, dry place, in tightly closed original containers, at a room temperature between 5°C to 40°C. Do not place in direct sunlight or near any heat source. Please do not return any used material to its original container.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.