



# A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road  
St Marys NSW 2760  
Australia

Ph: 1300 738 250 (Australia)  
Ph: +61 2 9833 9766 (International)  
Fax: 02 9623 3670

sales@chemtools.com.au  
www.chemtools.com.au

## TECHNICAL DATA SHEET

DECEMBER 2016

### PRODUCT NAME

DEOX™ R30 Dry Lube with PTFE

### PRODUCT RANGE

<b>Part Number</b>	<b>Available Size</b>
CT-R30-300	300g Aerosol



Refer to SDS for product safety guidelines

## DEOX™ R30 Dry Lube with PTFE

Chemtools® DEOX™ R30 Dry Lube is a powerfully effective Teflon™-based dry lubricant that resists high and low temperatures and is perfect for all weather applications. It is non-staining and non-oily and contains excellent film-forming and anti-seize properties.

DEOX™ R30 Dry Lube is fast drying with a low odour, and is free of silicone and chlorinated solvents. It bonds to most surfaces including metal, wood, rubber, plastic, and glass. The extremely low static coefficient of friction makes it a superb lubricant where low speeds and light loads are involved.

*Disclaimer: Teflon™ is a registered trademark of DuPont Corporation*

### FEATURES AND BENEFITS:

- Dry film lubricant
- Provides excellent anti-seize properties
- Convenient aerosol spray
- High load carrying properties
- Accelerates the running-in period

### APPLICATION:

- Sliding tracks
- Locks and catches
- Rollers
- Drawers and hinges
- Windows
- Conveyor belts

### PROPERTIES:

Appearance	Translucent white film	Specific Gravity	0.64
Odour	Mild Solvent	Flammable	Yes
Propellant	CO <sup>2</sup>	Paintable	No
Shelf Life	1 year + from date of manufacture		

**STORAGE:**

Store in closed containers, undercover, in a cool and dry environment.

**PRECAUTIONS:**

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the material.

**WARRANTY:**

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.