



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

MAY 2015

PRODUCT NAME

DEOX R44 Thick Film Lubricant

PRODUCT RANGE

Part Number	Available Size
CT-R44-300	300g Aerosol (CO ²)
CT-R44-400	400g Aerosol (Hydrocarbon)
CT-R44-1L	1 Litre
CT-R44-5L	5 Litres
CT-R44-20L	20 Litres
CT-R44-200L	200 Litres



Refer to SDS for product safety guidelines

DEOX R44 Thick Film Lubricant

Chemtools® DEOX R44 Thick Film Lubricant is a solvent free lube that provides long term protection and lubrication for all metal surfaces. This product is free of any harmful substances such as aliphatics, diesel, silicone, and kerosene. It has highly effective corrosion protection properties and is specially formulated to be used in most industrial, farming, marine, automotive, railway, aviation, mining, aerospace, and defence environments.

FEATURES AND BENEFITS:

- Australian made
- Superior corrosion protection
- Excellent lubrication properties
- Cleans and protects most metal surfaces

APPLICATIONS AND USES:

- Rust-proofing
- Boat trailers and other marine equipment
- Firearms
- White goods
- Sporting equipment
- Removes moisture from electrics
- Cleaning and protecting garden tools
- Storage protection
- Mining equipment
- Lubricate and protect antennas
- Drilling & Tapping fluid
- Battery terminals and wiring
- Timber preservation

PROPERTIES:

Flash Point	12°C
Boiling Point	>200°C
Appearance	Clear Pale Yellow Liquid
Odour	Low
Specific Gravity @ 20°C	0.82 – 0.85
Aerosol Propellant	CT-R44-300: CO ² CT-R44-400: Hydrocarbon

STORAGE:

Store in a cool, dry place, in tightly closed original containers at a room temperature between 5°C and 40°C. Do not place in direct sunlight or near any heat source. Do not return any used material to its original container.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the product's suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.