



VIKING® AUTO DARKENING WELDING HELMETS

WITH 4C™ LENS TECHNOLOGY

WELDING TECHNOLOGY
SOLUTIONS FOR ALL PHASES OF WELDING AND ENGINEERING EQUIPMENT

Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz



See Clearly Now

4C™ Lens Technology

The new 4C ADF Technology improves the performance of the lens in the 4 most important categories to the welder:

- 1. Clarity - Optical Clarity 1/1/1/1
- 2. Color - Real Color View
- 3. Carat - Light Weight
- 4. Cut - Even Shade From Any Angle

The 4C Lens Technology upgrade to Lincoln Electric's VIKING® welding helmets – including the 1840 series, 2450 series and 3350 series – improves visibility and reduces eye strain by minimizing the traditional lime green coloring in the helmet view screen.

4C technology is ideal for a range of industries such as general fabrication, power generation, shipbuilding, structural, offshore and pipeline that use multiple welding processes, including Stick, MIG and TIG. Whatever the task at hand, 4C technology gives you a clear view to productivity and quality.



Foose
Impostor™
K4181-3

Inactive State



Previous 1/1/1 Inactive



NEW 4C Inactive

Active State



Previous 1/1/1 Optical Clarity



NEW 4C 1/1/1 Clarity

WELDING TECHNOLOGY
SOLUTIONS AND ENGINEERING

Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz



A VISION FOR BETTER WELDS

Better Clarity, Real Color View

Now you can make a good view even better. Upgrading the VIKING 1840, 2450 and 3350 series with 4C technology preserves the existing 1-1-1 optical clarity rating, but improves visibility by reducing the lime green tint.

Easy On The Eyes

Improved visibility and less eye strain means greater comfort for the welder. This combined with an improved view of the weld puddle adds up to better welds.

Wide-Screen View

4C technology enables you to not only see better, but also see more. The large viewing area gives you a full range of vision in relation to the welding area, which enhances operator control.

Increased Battery Life

The longer you can see clearly, the more you can weld. And more welds mean higher productivity. Improvements to the ADF's circuitry enables more performance from the battery. Now you can keep welding, increase your productivity and get more from your helmet lens.

WELDING TECHNOLOGY
SUPPLIERS OF WELDING AND ENGINEERING EQUIPMENT



Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz



Cheater lens capable



Hard hat capable



Comfortable Headgear

Processes »

Stick, TIG, Pulsed TIG, MIG, Pulsed MIG, Flux-Cored, Gouging, Grinding, Plasma Cutting

Applications »

All

3350 Viking Helmets



3350 Black
K3034-3

Born to Weld™
K3616-3

Hot Rodder™
K4440-3

Steampunk™
K3428-3

Mojo®
K3101-3



Code Red®
K4034-3

Motorhead®
K3100-3

Twisted
Metal®
K3248-3

3350 All
American®
K3175-3

Jessi vs. the
Robot™
K3372-3



3350 White
Tail Camo™
K4412-3

Zombie™
K4158-3

Polar Arc™
K3255-3

Terracuda®
K3039-3

Impostor™
K4181-3

KEY FEATURES

The VIKING 3350, our top-of-the-line helmet series, provides the best optical clarity available in a welding helmet today and the largest viewing area in its class. The 3350 Series offers a pivot style headgear designed for greater comfort and optimal fit.

- 4C Lens Technology
- Perfect 1/1/1 optical clarity rating (EN379)
- Largest viewing area in the VIKING line
- Superior comfort with the pivot style headgear
- Longer battery life
- 3 year warranty



09 274 1246

info@weldingtechnology.co.nz

www.weldingtechnology.co.nz

2450/2450D Viking Helmets



2450 Black
K3028-3

Jessi the Welder™
K4437-3

Street Rod®
K3035-3

Heavy Metal®
K3029-3

Graveyard Shift®
K3099-3



2450 All
American®
K3174-3

2450 White
Tail Camo™
K4411-3



2450D Black
K3230-3



Comes with helmet bag,
Bandana and Lenses

KEY FEATURES

The VIKING 2450, the latest evolution in our mid-priced auto-darkening helmet line, provides the best optical clarity available in a welding helmet today. The 2450 Series offers an improved headgear for greater comfort and flexibility. Choose from six unique graphic designs.

- 4C Lens Technology
- Perfect 1/1/1 optical clarity rating [EN379]
- Fastest switching speed in its class
- Up to 28% larger viewing area versus competitive helmets
- Designed for long hours of comfortable wear with the new pivot style headgear
- 3 year warranty

With all the features of our standard 2450, the 2450D helmet gives you access to three modes – welding, cutting, and grinding – with a user-friendly LCD screen digital interface. Just one helmet with one cartridge produces a full spectrum shade 4-13 with variable sensitivity and delay.

WELDING TECHNOLOGY
SUPPLIERS OF WELDING AND ENGINEERING EQUIPMENT



Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz

1840 Viking Helmets



1840 Black
K3023-3

Aztec™
K4175-3

1840 All
American®
K3173-3



1840 Comes with helmet bag,
Bandana and Lenses

KEY FEATURES

The VIKING 1840, an economical auto-darkening helmet, provides operators with the best optical clarity available in a welding helmet today. External controls allow for quick and easy shade changes. The 1840 Series offers an improved headgear for greater comfort and optimal fit. Choose from our unique graphic designs.

- 4C Lens Technology
- Perfect 1/1/1 optical clarity rating (EN379)
- 16% larger viewing area than its competitor
- Pivot style head gear distributes weight evenly
- Convenient external shade control
- Lightweight and compact
- 3 year warranty

WELDING TECHNOLOGY
SUPPLIERS OF WELDING AND ENGINEERING EQUIPMENT



Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz

ACCESSORIES AND REPLACEMENT PARTS

Sales Number	Description	Dimensions	Package Qty.
KP3045-3	3350 SERIES ADF CARTRIDGE	STD 4 X 5	1
KP3044-1	3350 INSIDE CLEAR COVER LENS	94.7 x 89.7 x 1.0 mm [3.73 x 3.53 x .04 in]	5
KP2898-1	2450/2450D/3350 OUTSIDE CLEAR COVER LENS	114 x 133 x 1.0 mm [4.5 x 5.25 x .04 in]	5
KP2932-3	2450 SERIES ADF CARTRIDGE	STD 4 X 5	1
KP3243-2	2450D SERIES ADF CARTRIDGE	STD 4 X 5	1
KP2931-1	2450/2450D INSIDE CLEAR COVER LENS	98.5 x 66.5 x 1.0 mm [3.88 x 2.62 x .04 in.]	5
KP2931-1	2450D INSIDE CLEAR COVER LENS	98.5 x 66.5 x 1.0 mm [3.88 x 2.62 x .04 in]	5
KP2898-1	2450D OUTSIDE CLEAR COVER LENS	114 x 133 x 1.0 mm [4.5 x 5.25 x .04 in]	5
S27978-54	2450D BLACK REPLACEMENT SHELL	N/A	1
S27978-58	2450D OUTSIDE COVER LENS SEAL	N/A	1
S27978-55	2450D ADF HOLDER	N/A	1
KP2853-3	1840 ADF CARTRIDGE	DINS 110 X 90	1
KP2897-1	1840 INSIDE CLEAR COVER LENS	96 x 51.6 x 1.0 mm [3.78 x 2.03 x .04 in.]	5
KP3043-1	1840 OUTSIDE CLEAR COVER LENS	114 x 100 x 1.5 mm [4.5 x 3.94 x .06 in.]	5
KP3046-100	CHEATER LENS 1.00 MAG	2 X 4.25 FRAME, 1.0 MAG	1
KP3046-125	CHEATER LENS 1.25 MAG	2 X 4.25 FRAME, 1.25 MAG	1
KP3046-150	CHEATER LENS 1.50 MAG	2 X 4.25 FRAME, 1.5 MAG	1
KP3046-175	CHEATER LENS 1.75 MAG	2 X 4.25 FRAME, 1.75 MAG	1
KP3046-200	CHEATER LENS 2.00 MAG	2 X 4.25 FRAME, 2.0 MAG	1
KP3046-225	CHEATER LENS 2.25 MAG	2 X 4.25 FRAME, 2.25 MAG	1
KP3046-250	CHEATER LENS 2.50 MAG	2 X 4.25 FRAME, 2.5 MAG	1
KP2930-1	SWEATBAND	N/A	2
KP3908-1	HEADGEAR W/SWEATBAND	N/A	1
KP3047-1	HARD HAT ADAPTER	N/A	1
S27978-31	BLACK REPLACEMENT SHELL	N/A	1
S27978-32	OUTSIDE COVER LENS SEAL	N/A	1
S27978-33	ADF HOLDER	N/A	1

WELDING TECHNOLOGY
SUPPLIERS OF WELDING AND ENGINEERING EQUIPMENT



Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz

PRODUCT SPECIFICATIONS

Product Name	Optical Clarity	Lens Switching Speed (sec)	Variable Shade/ Control	Battery Replacement Type	Magnifying "Cheater" Capable Lens	Grind Mode Shade/ Control	Light Sensitivity Control	Delay Control Dark to Light (sec)	Arc Sensors	TIG Amp Rating	Cartridge Size in. (mm)	View Size in. (mm)	Temperature Range	Weight oz. (g)	Warranty
3350	1/1/1	1/25,000	5-13 Internal	1 CR2450 Replaceable Battery	Yes	3.5 / Internal	Continuous	0.1 - 1.0 Fully Adjustable	4	DC > 2 Amp AC > 2 Amp	US 5.25 x 4.50 (133 x 114)	3.74 x 3.34 (95 x 85)	Operating: -10°C - +55°C (14°F - 131°F) Storage: -20°C - +70°C (-4°F - 158°F)	21 (595)	3 Years
2450				2 CR2450 Replaceable Batteries								3.82 x 2.44 (97 x 62)			
2450D			4-13 Internal	2 CR2450 Replaceable Batteries		4 / Internal	Digital Display Control								
1840			9-13 Internal	1 CR2450 Replaceable Battery		3.5 / External	Continuous					2			

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company* is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

The operation of welding fume control equipment is affected by various factors including proper use and positioning of the equipment, maintenance of the equipment and the specific welding procedure and application involved. Worker exposure level should be checked upon installation and periodically thereafter to be certain it is within applicable OSHA PEL and ACGIH TLV limits.



Ph: 09 274 1246
info@weldingtechnology.co.nz
www.weldingtechnology.co.nz

22801 St. Clair Avenue • Cleveland, OH • 44117-1199 • U.S.A.

The Lincoln Electric Company

www.lincolnelectric.com