

VIPER™ CUT 30MkII Plasma Cutter

Key Features:

- CNC Connection
- 10 AMP Plug
- Pilot Arc Start
- 10mm Clean Cut
- 12mm Severance
- Standard / Perforated Cutting Modes
- 2T/4T Torch Controls
- Air Test



TECHNICAL DATA	
SKU	XA-CUT30VMK2
PRIMARY INPUT VOLTAGE	240V Single Phase
SUPPLY PLUG	10A
RATED INPUT POWER (kVA)	7.5
RATED OUTPUT VOLTAGE (V)	92
AIR FLOW DRAW OFF (L/min)	170
AIR FLOW PRESSURE (Bar)	5-6 (70-87 psi)
PROTECTION CLASS	IP21S
INSULATION CLASS	F
MINIMUM GENERATOR (kVA)	8.0
DINSE CONNECTOR	10/25
STANDARD	AS/NZ60974-1
WARRANTY (Years)	2

PLASMA CUT SPECIFICATIONS	
PLASMA CUT CURRENT RANGE	20-30A
PLASMA CUT DUTY CYCLE @ 40°C	15% @ 30A
MILD STEEL CUT THICKNESS	10mm
MILD STEEL SEVERANCE THICKNESS	12mm
ALUMINIUM CUT THICKNESS	6mm
ALUMINIUM SEVERANCE THICKNESS	8mm
STAINLESS STEEL CUT THICKNESS	6mm
STAINLESS STEEL SEVERANCE THICKNESS	8mm

SIZE & WEIGHT	
DIMENSIONS (mm)	534x166x343mm
WEIGHT (kg)	8.5kg

MACHINE FEATURES	
PLASMA ARC START	Pilot Arc
THERMAL OVERLOAD PROTECTION	Over Temperature Warning

Recommended Accessories



Plasma Cutter Air Filter

AT1000
AT50505

See page 17



SC40 Plasma Torch Spares Kit

XAPSK-SC40